

Graf. Garrison

Operating Instructions

Date:

Installation: _____

Unit: _____

Working Area:

Workshop

Workplace/Activity:

Repair / Maintenance / Storage

Hazardous Substance Group

Sealant and primer coat

Example: Sealing agent for vehicle body work parts / windows, cavity seal, under seal

Hazard for Human Health and the Environment



- Flammable
- Harmful to health/noxious after inhalation, swallowing and contact to skin
- Causes irritations to skin and respiratory tract



Protective Measures and Behaviour Rules



- During use wear **safety goggles** and **protective gloves**
- Avoid contact with eyes and skin
- Keep away from ignition sources – do not smoke
- Keep container tightly closed if not in use
- Only use in well ventilated areas



Behavior in Danger Situations



- **Accidental release:** Use adsorbent for cleaning of spillages/leakages of liquids (Spill Kit!), put contaminated adsorbent into designated waste container
- Provide adequate ventilation to area where spill occurred

EMERGENCY NUMBER: 117 (Fire Department)

NEXT PHONE: _____

First Aid



- After **eye contact:** Immediately flush thoroughly with plenty of water for at least 10 minutes, contact eye specialist
- After **skin contact:** Immediately wash with water and soap thoroughly, immediately take off contaminated clothes
- After **inhalation:** Remove to fresh air
- After **swallowing:** Rinse mouth thoroughly and then drink plenty of water, immediately get medical attention

EMERGENCY NUMBER: 117 (Fire Department)

NEXT PHONE: _____

Proper Disposal



Collect waste/residuals in a resistant, lockable and labelled container and keep at the HWAP prior to proper disposal.

Additional Remarks

Special information with reference to possible hazards for human health and environment as well as to hazard characteristics of the individual hazardous substances should also be taken from the **Material Safety Data Sheets (MSDSs)**. For further information please refer to "**General Operating Instructions**".